



Industrias Químicas Kupsa

☒ Aptdo. de correos 1081
26080 LOGROÑO. LA RIOJA (ESPAÑA).
☎ 945 62 22 25 Fax: 945 62 22 31
E-mail: kupsa04@kupsa.es

KUPSIROL® Serie RR Deep Matt U.V. Transparent Topcoat

Reference: **ZQ 1029 T**

Product description

Transparent deep matt U.V. curing topcoat for Rill roller application.

Components and/or Thinners

Product is already photo-initiated.

Suitable thinners: Solvon® Serie Reactivo DZ 7000 V

Physical-chemical characteristics

Density:	1.07 grs/cm ³ ±0.010
Solid contents:	91 %
Viscosity:	42 " ± 10 Ford4 at 20°C
Gloss:	8° ± 2, 60° angle

Application systems

Application by rill rollers production lines with coat thickness between 15 and 20 gr/m² on previously sanded primer or paper substrate.

Drying system

It is possible to have immediate drying with High Pressure U.V. lamps with speeds of line up to 6m/min per lamp.

Usage field

Flat pieces application lines.

Storing and packaging.

Hermetically closed container protected sources of light.

- *Maximum storing-time:* 180 days.
- *Available sizes:* 20 L metal drum.

Observations

With application grams smaller or higher than recommended, the drying can be deficient.

It allows reducing VOC emission to the air.